

Equus Flexigrout

Purpose & Areas Of Use:

An acrylic modified, non staining grout for use mainly with natural stone or composite stone pavers

Product:

A two component grout consisting of liquid (**Flexigrout Gauging Fluid**) and dry powder (**Premix M14**) products mixed together.

Process Compatibility:

Fully Compatible with **Equus Thermexx Adhesive** to complete the **Thermexx Stone** Paving process. Also compatible with most other adhesives. Contact the nearest Equus sales office for confirmation.

Colour:

Cementitious Grey.

Standard Pack:

Flexigrout Gauging Fluid – 20L jerricans (Other sizes by arrangement)

Premix M14 – 25kg bags

Physical Properties:

Liquid Material:

Volume Solids (% by Vol):	26%
Specific Gravity:	1.03
Flash Point:	Non combustable
Shelf Life:	Three years in original sealed containers, stored in cool conditions.

Surface Preparation:

Ensure that all gaps between stone pavers which are to be grouted are free of detritus and clean. Any relief joints must be filled or protected for future filling with the appropriate **Tremco flexible sealant** prior to commencing grouting.

Application Method:

Mixing:

Mix 3.3 litres of **Flexigrout Gauging Fluid** with each 25 kg bag of **Premix 14**. Add the gauging Fluid in two (2) or three (3) smaller amounts while mechanically mixing. Use a "jiffy" mixer or similar to obtain an even mix of "damp sawdust" consistency.

Application:

Tip the mixed material onto the paving surface and work the mix into the gaps. Using a tool of appropriate width compact this grout tightly between the pavers, adding more grout as appropriate to attain the required depth. When well ompacted, dampen the completed area to both wash the pavers and provide water to complete the curing process of the grout.

Health & Safety:

Equus Flexigrout Gauging Fluid is a non-flammable emulsion, is non-toxic, and safe to handle. When mixed with cementitious premixes, the normal precaution for skin care when handling cement based products, must be observed.

Equus Industries Ltd
PO Box 497
Frankston
Victoria 3199
Phone: 03 9706 6226 Fax 03 9706 4880
Email: tech-support@equus.com.au
Website: www.equus.com.au