



253

2pages

PRODUCT
DATA
SHEET

If the surface is to be subjected to very severe stresses, it is recommended to apply a three-coat system.

Keim Spezial-Fixativ is recommended as a diluent on difficult, poor and/or variably absorbent substrates.

Application conditions:

Ambient and substrate temperatures > + 5°C. Do not apply in direct sunlight or onto sun-heated substrates. Protect coated surfaces from direct sunlight, wind and rain during and after application.

Drying Times:

A dry time of at least 12 hours must be left between coats. In the case of pre-treatment with Keim Silangrund, the priming coat should be applied after approx. 4 hours.

Consumption:

For a two coat application on smooth substrate with Keim Granital per m²:

approx. 0.35kg Keim Granital

Approx. 0.03 ltr. Keim Fixativ or Keim Spezial Fixativ

The stated consumption values are for guidance and depend on the nature of the application method. Exact consumption values can only be determined by painting trial areas on the structure to be coated.

Cleaning of Tools:

Clean with plenty of water immediately after use.

During breaks, store tools in the paint or in water.

Third-party additives:

In order to preserve the specific characteristics of the Granital system, no other substances may be added.

Storage:

Storage life is approx. 12 months in a sealed container under cool, but frost-free conditions.

Protect from heat and direct sunlight.

Hazardous substances ordinance class

Not applicable

Transport Hazardous class

Not applicable

Disposal

EC Waste Code no. 08 01 12

Any residues must be emptied out of containers before recycling.

Safety Instructions:

Provide appropriate protection which are not to be coated (e.g glass, natural stone, ceramics, wood etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with water. Protect the eyes and skin from splashes. Keep out of reach of children.

Product code: M-SK 01

Edition 04/07

Equus Industries Ltd
PO Box 497 Frankston
Victoria 3199, Australia
Phone: 03 9706 6226 Fax 03 9706 4880
Email: tech-support@equus.com.au
Web: www.equus.com.au

The information in this product data sheet is based on the experience and testing of Keimfarben GnbH & Co.KG. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. Keimfarben reserve the right to alter or up-date information parameters and formulations at any time without notice. Equus Industries is the Agent and distributor for New Zealand and the Southern States of Australia only.