

Equus Interior Lo Sheen

Areas of Use:

An interior, low sheen/silk paint for use on most interior surfaces. Produces a smooth, tough, washable, burnish resistant finish.

Product:

A 100% acrylic, water based finish pigmented with titanium dioxide and inert extenders. It is a low odour product formulated for application at temperatures as low as 3°C.

Compatibility:

Use with Equus Gib Sealer, Chevaprime PBT and Chevaprime U depending upon surface to be coated.

May be applied as an interior topcoat to all Equus water-based texture finishes.

Colour:

Available in most BS5252 and BS2660 colours. Special colour matching is available, but may be subject to minimum batch quantities. Some very bright or strong colours may incur a colour surcharge.

Standard pack:

4, 10 and 20 litre plastic pails.

Physical Properties:

Solids (% by volume): 37.2%
Solids weight: 55.6%
Specific gravity: 1.42
Flash point: None - waterborne material
Shelf life: 3 years in original sealed containers.
Store in cool, dry conditions and protect from frost.

Applied Film:

Adhesion: Excellent to recommended primers, sealers and most previously painted surfaces.

Abrasion resistance: Very good

Durability: Excellent

Surface Preparation:

All surfaces to be coated must be cleaned to remove dirt, dust and any loose material. Ensure that the surfaces are also free of oil, grease or mould.

Primers:

For Gib board: Equus Gib Sealer
For timber, fibrous plaster, hardboard, particle board, fibreboard: Chevaprime PBT

For advice on application to other surfaces, contact the nearest Equus Office.

Application Properties:

By brush, speed brush, roller or conventional/airless spray.

Spreading rate: 10sqm/litre
No. of coats: Normally 2 coats
Dry film thickness/coat: 37 microns
Dry time - Touch dry: 1 hour
Recoat time: 2-4 hours
(dry times at 21°C and 50% relative humidity)

Application Conditions:

Do not apply at temperatures below 3°C or when temperatures are liable to fall below this while drying.

Health & Safety:

Equus Lo Sheen is a waterborne material with Low VOC, is non flammable and contains no mammalian toxic substances.

It requires no special storage conditions other than protection from excessive heat and frost. We recommend the use of barrier cream on exposed skin when handling this material.

Equus Industries Ltd
PO Box 497
Frankston 3199
Victoria
Phone: 03 9706 6226 Fax 03 9706 4880
Email: tech-support@equus.com.au
Web: www.equus.com.au