

# Equus WBSB

***Colourless, impregnating, soluble salt suppressant for mineral surfaces***

## **Purpose & Areas of Use:**

A penetrating, soluble salt suppressant for use on porous, even highly alkaline mineral substrates.

**Equus WBSB** restricts the capillary movement of salt impregnated moisture through the mineral substance.

## **Product:**

**Equus WBSB** is a waterbased and environmentally compatible mixture of silicone based chemicals, which are susceptible to hydrolysis. This only occurs after application to the substrate and the breaking of the emulsion, at which stage it converts to a very effective silicone resin water repellent.

## **Colour:**

Opaque white emulsion drying clear.

## **Standard Pack:**

4 litre and 20 litre

## **Physical Properties:**

### **Liquid Material:**

Appearance:	Milk white liquid
Specific Gravity:	approximately 1.0
Flash Point:	none – waterbased
pH:	7-8

## **Surface Preparation:**

Ensure that the surface to be treated is “wind dry” and free from dirt, grit, dust, grease etc, paints, form release agents, curing compounds, moss, lantence, algae etc must be removed.

## **Application Method:**

Apply undiluted, direct from the container.

Apply by brush or low pressure, non-atomising spray equipment  
(approx 40 – 70kpa)

Flood the surface. If using a brush do not brush out like paint. Apply evenly with steady strokes over the entire surface to completely wet/flood the surface.

Similarly with low pressure spraying, let the liquid flow down and evenly wet/flood the surface.

To ensure thorough impregnation, three coats are required, applied wet on wet, approximately 10 minutes apart, depending upon prevailing conditions.

## **Spreading Rate:**

Spreading rate will depend upon the porosity and subsequent absorbency of the substrate.

On aged porous brickwork, the consumption may be up to 2m<sup>2</sup>/litre initially.

The quantity of material required for the subsequent two coats may significantly reduce as each is applied.

The exact consumption rate can only be determined by application of an on-site test area.

## **Dry Time/Salt Suppressing Development:**

It will take **Equus WBSB** from a few days to some weeks to achieve full efficacy.

Water repellency on the surface begins building is soon as the water in the product evaporates and the emulsion breaks.

At 20°C and 60% relative humidity this will occur within 2 hours, protecting the substrate from water ingress through light rain; allowing the full salt suppressing nature of this product to build within the substrate.

## **Clean Up:**

Water

## **Health & Safety:**

**Equus WBSB** is a non-flammable emulsion and is non-toxic and safe to handle.

It is recommended however that suitable protective clothing be worn as well as eye protection and a quality barrier cream or gloves used on the hands.

Do not eat, drink or smoke while working with the product.

**Equus Industries Ltd**  
PO Box 497 Frankston  
Victoria 3199, Australia  
Phone: 03 9706 6226 Fax 03 9706 4880  
Email: [tech-support@equus.com.au](mailto:tech-support@equus.com.au)  
Web: [www.equus.com.au](http://www.equus.com.au)